



ARCHITECTURAL WINDOW FILM SPECIFICATIONS

SAFETY & SECURITY FILMS

	% Visible Light Transmission	% Total Solar Transmission	% Total Solar Reflectance	% Total Solar Absorbance	% Visible Light Reflectance INT/EXT	Winter U-Value	% Ultraviolet Protection (wavelengths 300-380nm)	% Glare Reduction	Shading Coefficient	% Solar Heat Gain Coefficient (SHGC)	% Total Solar Energy Rejection (TSER)	
Clear Series												
2M	89	83	8	9	9/9	1.07	94	1	0.99	0.86	14	
4M	89	82	8	10	9/9	1.07	99	1	0.98	0.85	15	
7M	89	82	8	10	9/9	1.07	99	1	0.97	0.85	15	
8M	88	81	9	10	10/10	1.06	99	2	0.96	0.84	16	
13M	88	80	9	11	10/10	1.06	99	2	0.96	0.83	17	
Symmetry™ Series (Dual-Reflective, Neutral)												
5M Symmetry 25	18	18	35	47	14/36	0.90	>99	80	0.35	0.31	69	
9M Symmetry 25	18	18	35	47	14/36	0.90	>99	80	0.35	0.30	70	
5M Symmetry 15	13	14	40	46	12/42	0.91	>99	86	0.30	0.26	74	
9M Symmetry 15	13	14	40	46	13/42	0.91	>99	86	0.31	0.27	73	
Silver Series (Reflective, Silver)												
5M Silver 20	13	10	56	34	65/62	0.87	>99	86	0.21	0.19	81	
9M Silver 20	13	10	55	35	65/61	0.87	>99	86	0.22	0.19	81	
Anti-Graffiti Series												
4M Anti-Graffiti	89	83	9	8	10/10	1.04	89	1	0.98	0.85	15	
6M Anti-Graffiti	89	82	9	9	10/10	1.04	90	1	0.98	0.85	15	

EASTMAN

suntekfilms.com

Data captured using National Fenestration Rating Council's (NFRC) guidelines and calculated for single pane, nominal 1/8 inch (3mm) clear glass. Reported values are taken from representative product samples and are subject to normal manufacturing variances. Actual performance will vary based on a number of factors, including glass type and properties. ©2021 Eastman Performance Films, LLC. Product brands referenced herein with a ™ or ® symbol are trademarks of Eastman Chemical Company or its subsidiaries. All other trademarks are the property of their respective owners. All rights reserved. No liability is accepted for errors. 06/21